CE

Harmonised Product Standard

# EN 14351-1:2006+A2:2016

# Declaration of Performance

Type of construction product:

Entrance doors and Patio doors

**VELFAC Classic Wood**
**triple-glazed**

DOP nr.:
**D-EK-V-UK-20260601**

The performance of the Entrance doors and Patio doors in the product line VELFAC Classic Wood triple-glazed are in conformity with the performances declared on the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.

System of assessment and verification of constancy of performance of the construction product:
(AVCP) System 3

Intended use:
For domestic and commercial buildings

Manufacturer:

## DOVISTA A/S

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):

NB 1235 - Technological Institute, Denmark

Name of authorized representative: DOVISTA (UK) Ltd., VAT No. GB 493346816, Mr Henrik Kjeldsen
Address, Authorized representative: Ground Floor, THE FORUM, 9 Lancaster Way, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU +44 01480 759511

Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

1. June 2026

Horsens

Signed on behalf of DOVISTA A/S

Allan Lindhard Jørgensen
CEO, DOVISTA A/S

## Declaration of Performance VELFAC Classic Wood; triple-glazed

**D-EK-V-UK-20260601**

| Opening function | 4.2 Resistance to windload | 4.5 Water tightness | 4.6 Dangerous substances | 4.8 Load bearing capacity of safety devices | 4.11 Acoustic performance | 4.12 * Thermal transmittance coefficient | 4.13 * Radiation properties | 4.14 Air permeability |
|---|---|---|---|---|---|---|---|---|
| **EDFI** **Flush door, inward opening, 1-leaf** | | | | | | | | |
| Declared value | Class C4 (1600 Pa) | Class 9A (600 Pa) | None | N/A | NPD | 0,61 (W/m2K) | - | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/244214-6/2024-Sep. | DTI/244214-6/2024-Sep. | - | - | - | 0108/688346V, 2016-03-23 | - | DTI/244214-6/2024-Sep. |
| Tested size (mm), WxH | 950 x 2185 | 950 x 2185 | - | - | - | 1230 x 2180 | - | 950 x 2185 |
| **EDFI-2** **Flush door, inward opening, 2-leaf** | | | | | | | | |
| Declared value | Class C4 (1600 Pa) | Class 9A (600 Pa) | None | N/A | NPD | 0,61 (W/m2K) | - | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/244213-4/2024-Jun. | DTI/244213-4/2024-Jun. | - | - | - | 0108/688346V, 2016-03-23 | - | DTI/244213-4/2024-Jun. |
| Tested size (mm), WxH | 1880 x 2190 | 1880 x 2190 | - | - | - | 1230 x 2180 | - | 1880 x 2190 |
| **EDFO** **Flush door, outward opening, 1-leaf** | | | | | | | | |
| Declared value | Class C4 (1600 Pa) | Class 9A (600 Pa) | None | N/A | NPD | 0,59 (W/m2K) | - | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/244211-1/2024-May | DTI/244211-1/2024-May | - | - | - | 0108/688346V, 2016-03-23 | - | DTI/244211-1/2024-May |
| Tested size (mm), WxH | 1200 x 2400 | 1200 x 2400 | - | - | - | 1230 x 2180 | - | 1200 x 2400 |

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet ”4.11, Acoustic performance”

Copyright DOVISTA A/S

## Declaration of Performance VELFAC Classic Wood; triple-glazed

**D-EK-V-UK-20260601**

| Opening function | 4.2 Resistance to windload | 4.5 Water tightness | 4.6 Dangerous substances | 4.8 Load bearing capacity of safety devices | 4.11 Acoustic performance | 4.12 * Thermal transmittance coefficient | 4.13 * Radiation properties | 4.14 Air permeability |
|---|---|---|---|---|---|---|---|---|
| **EDFO-2** **Flush door, outward opening, 2-leaf** | | | | | | | | |
| Declared value | Class C4 (1600 Pa) | Class 7A (300 Pa) | None | N/A | NPD | 0,59 (W/m2K) | - | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/244214-1/2024-Sep. | DTI/244214-1/2024-Sep. | - | - | - | 0108/688346V, 2016-03-23 | - | DTI/244214-1/2024-Sep. |
| Tested size (mm), WxH | 2337 x 2400 | 2337 x 2400 | - | - | - | 1230 x 2180 | - | 2337 x 2400 |
| **EDI** **Glazed entrance door, inward opening, 1-leaf** | | | | | | | | |
| Declared value | Class C4 (1600 Pa) | Class 9A (600 Pa) | None | N/A | NPD | 0,84 (W/m2K) | Gg 0,53 / LTg 0,74 | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/332468-1/2025-Sep. | DTI/332468-1/2025-Sep. | - | - | - | 0108/688346V, 2016-03-23 | 0108/688346V, 2016 | DTI/332468-1/2025-Sep. |
| Tested size (mm), WxH | 1200 x 2400 | 1200 x 2400 | - | - | - | 1230 x 2180 | - | 1200 x 2400 |
| **EDI-2** **Glazed entrance door, inward opening, 2-leaf** | | | | | | | | |
| Declared value | Class B4 (1600 Pa) | Class 9A (600 Pa) | None | N/A | NPD | 0,84 (W/m2K) | Gg 0,53 / LTg 0,74 | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/332468-2/2025-Sep. | DTI/332468-2/2025-Sep. | - | - | - | 0108/688346V, 2016-03-23 | 0108/688346V, 2016 | DTI/332468-2/2025-Sep. |
| Tested size (mm), WxH | 2400 x 2400 | 2400 x 2400 | - | - | - | 1230 x 2180 | - | 2400 x 2400 |

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet ”4.11, Acoustic performance”

Copyright DOVISTA A/S

## Declaration of Performance VELFAC Classic Wood; triple-glazed

**D-EK-V-UK-20260601**

| Opening function | 4.2 Resistance to windload | 4.5 Water tightness | 4.6 Dangerous substances | 4.8 Load bearing capacity of safety devices | 4.11 Acoustic performance | 4.12 * Thermal transmittance coefficient | 4.13 * Radiation properties | 4.14 Air permeability |
|---|---|---|---|---|---|---|---|---|
| **EDO** **Glazed entrance door, outward opening, 1-leaf** | | | | | | | | |
| Declared value | Class C4 (1600 Pa) | Class 9A (600 Pa) | None | N/A | NPD | 0,82 (W/m2K) | Gg 0,53 / LTg 0,74 | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/268669-3/2024-Okt. | DTI/268669-3/2024-Okt. | - | - | - | 0108/688346V, 2016-03-23 | 0108/688346V, 2016 | DTI/268669-3/2024-Okt. |
| Tested size (mm), WxH | 1200 x 2400 | 1200 x 2400 | - | - | - | 1230 x 2180 | - | 1200 x 2400 |
| **EDO-2** **Glazed entrance door, outward opening, 2-leaf** | | | | | | | | |
| Declared value | Class C4 (1600 Pa) | Class 9A (600 Pa) | None | N/A | NPD | 0,82 (W/m2K) | Gg 0,53 / LTg 0,74 | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/244214-2/2024-Sep. | DTI/244214-2/2024-Sep. | - | - | - | 0108/688346V, 2016-03-23 | 0108/688346V, 2016 | DTI/244214-2/2024-Sep. |
| Tested size (mm), WxH | 2337 x 2400 | 2337 x 2400 | - | - | - | 1230 x 2180 | - | 2337 x 2400 |
| **PDI** **Patio door, inward opening, 1-leaf** | | | | | | | | |
| Declared value | Class C4 (1600 Pa) | Class 9A (600 Pa) | None | N/A | NPD | 0,84 (W/m2K) | Gg 0,53 / LTg 0,74 | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/352263-1/2026-Jan. | DTI/352263-1/2026-Jan. | - | - | - | 0108/688346V, 2016-03-23 | 0108/688346V, 2016 | DTI/352263-1/2026-Jan. |
| Tested size (mm), WxH | 1200 x 2400 | 1200 x 2400 | - | - | - | 1230 x 2180 | - | 1200 x 2400 |

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet ”4.11, Acoustic performance”

Copyright DOVISTA A/S

## Declaration of Performance VELFAC Classic Wood; triple-glazed

**D-EK-V-UK-20260601**

| Opening function | 4.2 Resistance to windload | 4.5 Water tightness | 4.6 Dangerous substances | 4.8 Load bearing capacity of safety devices | 4.11 Acoustic performance | 4.12 * Thermal transmittance coefficient | 4.13 * Radiation properties | 4.14 Air permeability |
|---|---|---|---|---|---|---|---|---|
| **PDI-2** **Patio door, inward opening, 2-leaf** | | | | | | | | |
| Declared value | Class B4 (1600 Pa) | Class 9A (600 Pa) | None | N/A | NPD | 0,84 (W/m2K) | Gg 0,53 / LTg 0,74 | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/352263-2/2026-Jan. | DTI/352263-2/2026-Jan. | - | - | - | 0108/688346V, 2016-03-23 | 0108/688346V, 2016 | DTI/352263-2/2026-Jan. |
| Tested size (mm), WxH | 2400 x 2400 | 2400 x 2400 | - | - | - | 1230 x 2180 | - | 2400 x 2400 |
| **PDO** **Patio door, outward opening, 1-leaf** | | | | | | | | |
| Declared value | Class C4 (1600 Pa) | Class 9A (600 Pa) | None | N/A | NPD | 0,82 (W/m2K) | Gg 0,53 / LTg 0,74 | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/244213-1/2024-Jun. | DTI/244213-1/2024-Jun. | - | - | - | 0108/688346V, 2016-03-23 | 0108/688346V, 2016 | DTI/244213-1/2024-Jun. |
| Tested size (mm), WxH | 1200 x 2400 | 1200 x 2400 | - | - | - | 1230 x 2180 | - | 1200 x 2400 |
| **PDO-2** **Patio door, outward opening, 2-leaf** | | | | | | | | |
| Declared value | Class C4 (1600 Pa) | Class 7A (300 Pa) | None | N/A | NPD | 0,82 (W/m2K) | Gg 0,53 / LTg 0,74 | Class 4 (±600 Pa) |
| Classification standard | EN 12210:2016 | EN 12208:2016 | - | - | - | - | - | EN 12207:2016 |
| Test standard | EN 12211:2016 | EN 1027:2016 | - | - | - | EN ISO 10077-2: 2003/2012 | - | EN 1026:2016 |
| Notified body | NB 1235 | NB 1235 | - | - | - | NB 1235 | - | NB 1235 |
| Test report | DTI/244211-4/2024-May | DTI/244211-4/2024-May | - | - | - | 0108/688346V, 2016-03-23 | 0108/688346V, 2016 | DTI/244211-4/2024-May |
| Tested size (mm), WxH | 2337 x 2400 | 2337 x 2400 | - | - | - | 1230 x 2180 | - | 2337 x 2400 |

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet ”4.11, Acoustic performance”

Copyright DOVISTA A/S