COR VISION
SYSTEM

Sightlines
Frame depth 116 mm / 182 mm 3 rails
Sash depth 37 mm
Interlock 20 mm
Polyamide strip length
16 / 24 mm
Profile thickness
Door 1.7 mm
Glazing
Max. 30 mm, Min. 26 mm
Maximum sash dimensions
Width (L) 2,500 mm, Height (H) 3,000 mm
Maximum sash weight
320 kg

Consult maximum weight and dimensions according to typologies



CORTIZO



CORTIZO | **COR VISION** SYSTEM

CORTIZO

Thermally broken minimalist sliding system that provides maximum luminosity with a minimal aluminium interlock profile. It has an elegant design only 20 mm sightline and offers the possibility of an inlaid closing system and of hiding the frame along the perimeter.

Possibility of locking system in the interlock, thus allowing the concealment of the sashes in the frame from a frontal view. Possibility of embedded locking system which facilitates the sashes crossing.

PAS24

- High thermal & acoustic performance
- Maximized glazed surface
- Stainless steel adjustable wheels
- 20 mm interlock
- Hidden track possibility



BFRC Rating
kWh/(m²·yr)

≥20	A	++
>10 to 20	A	+
0 to <10	A	✓
-10 to <0	B	
-20 to <-10	C	
-30 to <-20	D	
-50 to <-30	E	

Double glazing



FEATURES

U-value		Uw ≥ 1.3 (W/m²K)
Acoustic insulation		Rw up to 41 dB
Air permeability		Class 4
Watertightness		Class 7A
Wind resistance		Class C5
Security test	PAS24	Passed

Reference test 1.23 x 1.55 m / 1 sash + 1 fixed light



INTERLOCK HANDLE



SECURITY
HARDWARE



FLUSH SECURITY
HARDWARE

HIDDEN TRACK SOLUTION



BESPOKE DRAINAGE SOLUTION



INTERLOCK HANDLE



DOUBLE TRACK





OPENING POSSIBILITIES



Sliding
Possibility of 1, 2 or 3 rails
Possibility of interior and exterior corner sash at 90° without mullion
Pocket possibility

POSSIBILITIES

ACCESSIBILITY