Harmonized Product Standard

BS EN 14351-1:2006 +A2:2016

Declaration of Performance

Type of construction product:
Entrance doors and Patio doors

VELFAC SIGNATURE
triple-glazed

DOP no.:

D-FAC-SIGN-UK-20260101

The performance of the Entrance doors and Patio doors in product line VELFAC SIGNATURE; triple-glazed are in conformity with the declared in the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.
System of assessment and verification of constancy of performance of the construction product:
(AVCP) System 3

Intended use:
For domestic and commercial buildings

Manufacturer:

DOVISTA A/S

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):
NB 1314, NB 1235

Name of authorized representative: DOVISTA (UK) Ltd., VAT No. GB 493346816, Mr Henrik Kjeldsen
Address, Authorized representative: Ground Floor, THE FORUM, 9 Lancaster Way, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU +44 01480 759511

Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

01 oktober 2025

Horsens

Signed on behalf of DOVISTA A/S

Allan Lindhard Jørgensen
CEO, DOVISTA A/S

Declaration of Performance VELFAC SIGNATURE; triple-glazed

Opening function	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
SD Sliding door								
Declared value	Class B3 (1200 Pa)	Class 9A (600 Pa)	None	N/A	NPD	0,88 (W/m2K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	-	EN 1026:2016
Notified body	NB 0621	NB 0621	-	-	-	NB 1235	-	NB 0621
Test report	element/WIL 544011/2024-Jun.	element/WIL 544011/2024-Jun.	-	-	-	0108/813504/2018-Jun.	0108/813504/2018-Jun.	element/WIL 544011/2024-Jun.
Tested size (mm), WxH	4780 x 2500	4780 x 2500	-	-	-	2500 x 2180	-	4780 x 2500

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006 +A1:2010.

** Declared values see sheet ”4.11, Acoustic performance”

Copyright DOVISTA A/S