





# **ASS 70 HI**

The highly thermally insulated aluminium lift-and-slide system Schüco ASS 70.HI with its perfect watertightness, excellent sound reduction and burglar resistance up to WK2 is second to none.  $U_d$  values < 1.3 W/m²K are possible due to the new modular profile insulation. With large opening widths and easy operation, Schüco ASS 70.HI offers new system solutions for large projects and luxury homes.

## **ASS 70 HI**







#### Product features and benefits

- Lift-and-slide system with narrow profile face widths
- · Basic depth of vent profile of 70 mm
- Basic depth of outer frame profile from 160 mm
- Wide range of designs based on single, double and triple track outer frames
- · Wide choice of colours different colours inside and outside
- Greater flexibility for project work due to the option for the customer to roll the profiles together
- Modular profile insulation
- Glass thickness up to 52 mm
- Watertightness up to class E 750 in accordance with DIN EN 12208 (depending on the design)
- Sound insulation in accordance with DIN EN ISO 140-03 and DIN EN ISO 717-1,  $\rm R_w \le 44~dB$

#### Technical data

Test	Value
Thermal insulation	$U_f$ from 2,16 W/(m <sup>2</sup> K)
	$U_w < 1.3 \text{ W/m}^2\text{K} (U_g = 0.7 \text{ W/m}^2\text{K}, \psi = 0.05 \text{ W/mK})$
Basic depth	Basic depth of vent profile 70 mm
Vent size (WxH)	Vent sizes up to 9 m <sup>2</sup> *
Vent weight	400 kg*
Security class	WK2 in accordance with DIN E ENV 1627*

depending on the design

#### Altitude Aluminium offer a wide range of Aluminium products for todays Grand Design Projects including:

Aluminium Windows • Sliding Doors • Folding/Bifolding Doors • Curtain Walling

Balconies • Balustrades • Structural Glazing • Rooflights

Altitude Aluminium • Access House • Aviation Park • Flint Road • Chester • CH4 OGZ

\*\*T 0800 2888 066 \*\*E quote@altitudealuminium.co.uk

### www.altitudealuminium.co.uk







